




Floor Standing Type - Fix Speed

The latest innovation from the world leader in air conditioning. Toshiba, introduces the all-new floor standing split air conditioning system. The RAV-xxxFS, premium design, inside and out, will provide you with cool comfort via a variety of control functions.



ELECTRONIC THERMOSTAT

Standard supplied with new, user friendly, large LCD display control panel easy to read the temperature from distance or even in the dark.

FEATURES:

- **SWING MODE**, With automatically Left/Right ensure coolness throughout the room.
- **INDOOR AIR QUALITY**, Washable filter enhances easily to maintenance.
- **AUTO FAN**, Adjustable Fan Speed with cools down the room quickly.
- **TURBO**, This function can boost cooling speed in a short period, and makes the room cool down rapidly.
- **TIME DELAY**, installed safety protection system, protects and prolongs usage life of compressor by delaying it for 3 minutes before restarting.
- **SLIM DESIGN**, New slim design blended to your of any room.
- **DURABLE**, Durable anti-rust casing helps the unit last longer.
- **MICROPROCESSOR**, enables precise temperature control up to 1 degree Celcius.

SPECIFICATIONS

Model Name		Indoor Unit	RAV-240FS-V	RAV-360FS-V	RAV-360FS-V	RAV-480FS-V	RAV-600FS-V
		Outdoor Unit	RAV-240ASP-V	RAV-360ASP-V	RAV-360AS8-V	RAV-480AS8-V	RAV-600AS8-V
Cooling Capacity		Btu/h	24200	36200	36200	49000	60000
Electrical Characteristics	Power Consumption	kW	2.18	3.14	3.14	5.30	5.50
	Operating Current	A	10.4	14.7	5.6	9.5	10.3
	EER/COP	W/W	3.26	3.38	3.38	2.71	3.20
		Btu/h/W	11.10	11.53	11.53	9.25	10.91
Indor Unit Dimensions (Height x Width x Depth)		mm	1800 x 570 x 330	1800 x 690 x 330	1800 x 690 x 330	1800 x 780 x 390	1800 x 780 x 390
Weight		kg	48.5	66.5	66.5	86.5	90
Standard Air Flow		m ³ /h	800	1200	1200	1600	2000
Sound Pressure Level (Turbo/High/Med/Low)		dB(A)	50/45/42/38	53/47/44/41	53/47/44/41	55/49/45/42	56/50/46/43
Connecting Pipe Dia., Gas/Liquid Side		mm	ø15.9/ø9.5	ø15.9/ø9.5	ø15.9/ø9.5	ø19.1/ø9.5	ø19.1/ø9.5
Standard Pipe Length		m	7.5	7.5	7.5	7.5	7.5
Maximum Pipe Total Length		m	25	30	30	30	50
Maximum Height Difference		m	10	20	20	20	30
Outdoor Unit Dimensions (Height x Width x Depth)		mm	630 x 800 x 300	890 x 900 x 320	890 x 900 x 320	890 x 900 x 320	1340 x 900 x 320
Weight		kg	43	63	63	73	103
Sound Pressure Level		dB(A)	52	55	55	57	63
Operating Range		°C	21~43	21~43	21~43	21~43	21~43

Rate conditions cooling: Indoor air temperature 27°C DB / 19°C WB, Outdoor air temperature 35°C DB

Dealer:

PT Berca Carrier Indonesia

Head Office:

Gedung Pusat Niaga 4th Floor, Arena PRJ Kemayoran, Jakarta 10610, Indonesia. Telp. (62) 21 2664 5888

✉ contact@carrier.co.id

🌐 www.carrier.co.id

Service & Parts Center:

Jalan Agung Timur II, Blok O-1, No. 40 - 41 Sunter, Jakarta 14350, Indonesia. Telp. (62) 21 2660 8088