



# i-Vu® Building Automation System

## UPC Open

### Integrated BACnet Communications Card



Connecting your Carrier equipment to a BACnet MS/TP network has never been easier. Simply connect the UPC Open to the BACnet network, and your Carrier equipment is ready to integrate seamlessly into the i-Vu Building Automation System or any other BACnet Building Automation System.



### Features and Benefits

- Factory-installed option on rooftops, air-cooled chillers, and water-cooled chillers
- Pre-programmed to share equipment data with any BACnet Building Automation System - no on-site engineering required
- Supports Carrier communicating space sensors with field programming:
  - Ideal for single zone rooftop applications
  - Available in 4 flavors, 2 of which have large, easy-to-read LCD displays
- Features a hidden communication port for network commissioning
- Supports plug-and-play connectivity to Carrier's i-Vu Building Automation System:
  - Integrated air source linkage algorithm
  - Built-in user interface graphics, diagnostic trends and alarms
  - Built-in demand limiting and inherent support for i-Vu Tenant Billing

### Specifications

<b>Communication Ports</b>	<b>BAS Port (Port 1A):</b> EIA-485 port for BACnet MS/TP communications, Baud rate is DIP switch selectable. <b>Local Access port:</b> For system start-up and troubleshooting; <b>Rnet port:</b> For connecting Carrier communicating space sensors.
<b>Protection</b>	Incoming power and network connections are protected by non-replaceable internal solid-state polyswitches that reset themselves when the condition that causes a fault returns to normal.
<b>Real Time Clock</b>	Battery-backed real time clock keeps track of time in event of power failure
<b>Battery</b>	10-year Lithium CR2032 battery provides a minimum of 10,000 hours of trend data & time retention during power outages
<b>Status Indicators</b>	LED status indicators for power, network communication, run status, and errors
<b>Controller Addressing</b>	Rotary DIP switches set BACnet MS/TP MAC address of controller
<b>Listed by</b>	UL916 (Canadian Std C22.2 No. 205-M1983), CE, FCC Part 15 – Subpart B – Class A
<b>Environmental Operating Range</b>	<b>Operating:</b> -22° to 150°F (-30° to 66°C), 10–95% relative humidity, non-condensing <b>Storage:</b> -24° to 140°F (-30° to 60°C), 10–95% relative humidity, non-condensing
<b>Power Requirements</b>	24 VAC ± 10%, 50-60Hz, 10 VA power consumption 26 VDC (25V min, 30V max), Single Class 2 source only, 100 VA or less

For more information, contact your local Carrier Controls Expert.

Controls Expert Locator:  
[www.carrier.com/controls-experts](http://www.carrier.com/controls-experts)